

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number  
**WO 2004/041007 A2**

- (51) International Patent Classification<sup>7</sup>: **A24D**
- (21) International Application Number:  
PCT/US2003/034290
- (22) International Filing Date: 30 October 2003 (30.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/422,497 31 October 2002 (31.10.2002) US
- (71) Applicant (for all designated States except US): **PHILIP MORRIS PRODUCTS S.A.** [CH/CH]; Quai Jeanrenaud 3, CH-2000 Neuchatel (CH).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **WOODSON, Beverley, C.** [US/US]; 656 Lake Caroline Drive, Ruther Glen, VA 22546 (US). **NEWMAN, Deborah, J.** [US/US]; 11866 Centennial Road, Prince George, VA 23875 (US).
- (74) Agents: **SKIFF, Peter, K.** et al.; Burns, Doane, Swecker & Mathis, L.L.P., P.O. Box 1404, Alexandria, VA 22314-1404 (US).


- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,

[Continued on next page]

(54) Title: **ELECTRICALLY HEATED CIGARETTE INCLUDING CONTROLLED-RELEASE FLAVORING**



(57) Abstract: Electrically heated cigarettes used in an electrical smoking system include a flavoring-release additive and sorbent effective to remove one or more gas-phase constituents of mainstream tobacco smoke. The flavoring-release additive includes at least one flavoring. The flavoring is released in the cigarette upon the flavoring-release additive reaching at least a minimum temperature during smoking. The flavoring-release additive can have various forms including, for example, beads, films and inclusion complexes. Electrical smoking systems including the electrically heated cigarettes, methods of making the cigarettes, and methods of smoking the cigarettes are also provided.

WO 2004/041007 A2



RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

**Published:**

- without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

-1-

## ELECTRICALLY HEATED CIGARETTE INCLUDING CONTROLLED-RELEASE FLAVORING

### BACKGROUND

5 [0001] Traditional cigarettes are smoked by lighting an end of a wrapped tobacco rod and drawing air predominately through the lit end by suction at a mouthpiece end of the cigarette. Traditional cigarettes deliver smoke as a result of combustion, during which tobacco is combusted at temperatures that typically exceed 800°C during a puff. The heat of combustion releases various gaseous  
10 combustion products and distillates from the tobacco. As these gaseous products are drawn through the cigarette, they cool and condense to form an aerosol, which provides the flavors and aromas associated with smoking.

[0002] Traditional cigarettes produce sidestream smoke during smoldering between puffs. Once lit, they normally are fully consumed or discarded.  
15 Relighting a traditional cigarette is possible, but is not desirable for subjunctive reasons including flavor, taste and odor.

[0003] An alternative to the more traditional cigarette is the electrically heated cigarette used in electrical smoking systems. As compared to traditional cigarettes, electrical smoking systems significantly reduce sidestream smoke, and  
20 also permit smokers to suspend and reinitiate smoking as desired. Exemplary electrical smoking systems are disclosed in commonly-assigned U.S. Patents Nos. 6,026,820; 5,988,176; 5,915,387; 5,692,526; 5,692,525; 5,666,976; 5,499,636; and 5,388,594, each of which is hereby incorporated by reference in its entirety. Electrical smoking systems include an electrically powered lighter and an  
25 electrically heated cigarette, which is constructed to cooperate with the lighter. It is desirable that electrical smoking systems be capable of delivering smoke in a

-2-

manner similar to the smoker's experiences with traditional cigarettes, such as by providing an immediacy response (smoke delivery occurring immediately upon draw), a desired level of delivery (that correlates with FTC tar level), a desired resistance to draw (RTD), as well as puff-to-puff and cigarette-to-cigarette consistency.

[0004] Volatile flavorings have been incorporated in traditional cigarettes to add flavors and aromas to mainstream and sidestream tobacco smoke. See, for example, U.S. Patents Nos. 3,006,347; 3,236,244; 3,344,796; 3,426,011; 3,972,335; 4,715,390; 5,137,034; 5,144,964; and 6,325,859, and commonly-owned International Publication No. WO 01/80671. The added flavorings are desirably volatilized when the cigarette is smoked. However, volatile flavorings tend to migrate in the cigarette to other components and possibly through the entire cigarette. Volatile flavorings can be lost from cigarettes during storage and distribution at ordinary conditions prior to smoking of the cigarettes. The degree of migration of volatile flavorings in cigarettes depends on different factors, including the flavoring's vapor pressure, the solubility of the flavoring in other components of the cigarette, and temperature and humidity conditions. In addition, a large portion of the added flavoring can be lost to the side stream smoke in traditional cigarettes.

[0005] Flavorings that have been incorporated in traditional cigarettes also can chemically and/or physically deteriorate by contacting and/or reacting with other components of the cigarette, as well as with the environment. For example, activated carbon has been incorporated in traditional cigarettes to remove gas-phase constituents from mainstream smoke. However, flavorings that have been incorporated in the cigarettes along with the activated carbon have been adsorbed by the activated carbon, clogging pores of the activated carbon and consequently

-3-

deactivating the activated carbon, thereby diminishing its ability to filter tobacco smoke.

[0006] For the foregoing reasons, flavorings that have been incorporated in traditional cigarettes have not been totally satisfactorily delivered to the smoker.

5 Consequently, the flavorings incorporated in some traditional cigarettes have not satisfactorily provided the desired taste effect to the smoker and the flavorings' desired value to the subjective quality of the cigarette has been less than desired. Due to the flavoring loss, the uniformity of flavored cigarettes has not been totally satisfactory. In addition, the sorption of flavorings by sorbents in the cigarettes has  
10 deactivated the sorbents and thereby reduced their ability to remove gas phase constituents from tobacco smoke.

#### SUMMARY

[0007] In view of the above-described problems that have been encountered in  
15 some traditional cigarettes including flavorings and those also including sorbents, an electrically heated cigarette is provided, which includes a sorbent and a controlled-release flavoring. In a preferred embodiment, the electrically heated cigarette comprises a sorbent and a flavoring incorporated in the cigarette in a form that preferably minimizes release and migration of the flavoring in the  
20 cigarette prior to smoking, for example, at ambient conditions, and thus preferably minimizes deactivation of the sorbent by the flavoring. In addition, the flavoring preferably is released in the cigarette in a controlled manner during smoking. Consequently, the flavoring preferably enhances subjective characteristics of the cigarette while the sorbent maintains its ability to remove gas-phase constituents  
25 from mainstream smoke.

[0008] A preferred embodiment of the electrically heated cigarette comprises at least one sorbent and a flavoring-release additive including one or more flavorings.

-4-

The flavoring is releasable in the cigarette upon the flavoring-release additive being heated to at least a minimum temperature, which occurs during smoking of the cigarette.

5 [0009] The flavoring-release additive can be incorporated in various forms in the electrically heated cigarette. In one preferred embodiment, the flavoring-release additive comprises beads. In another preferred embodiment, the flavoring-release additive is a film. In yet another preferred embodiment, the flavoring-release additive is an inclusion complex including a selected host molecule, and the flavoring as a guest molecule in the inclusion complex.

10 [0010] In another preferred embodiment, two or more different flavoring-release additives having different flavoring release temperatures are located at different locations in an electrically heated cigarette that reach different temperatures from each other. The flavoring-release additives can be located at locations in the electrically heated cigarette that reach the flavoring release temperature for those  
15 flavoring-release additives. Accordingly, the flavoring-release additive can provide efficient, controlled release of the flavoring during smoking.

[0011] The electrically heated cigarette can comprise various sorbents. By providing the flavoring in the flavoring-release additive, which preferably minimizes release and/or migration of the flavoring until the flavoring-release  
20 additive reaches the flavoring release temperature, the flavoring is preferably substantially prevented from being sorbed by, and thus deactivating, the sorbent, thereby not adversely affecting the sorbent's ability to remove selected gas-phase constituents from mainstream tobacco smoke. In addition, because the flavoring is temperature released in the cigarette, it can be effectively delivered to a smoker in  
25 a controlled manner during puff cycles of the cigarette.

-5-

[0012] A preferred embodiment of an electrical smoking system comprises a lighter and at least one electrically heated cigarette including at least one sorbent and a flavoring-release additive.

5 [0013] A preferred embodiment of a method of making an electrically heated cigarette comprises incorporating a sorbent and a flavoring-release additive into an electrically heated cigarette.

#### BRIEF DESCRIPTION OF THE DRAWINGS

10 [0014] FIG. 1 illustrates a preferred embodiment of an electrically heated cigarette for use in an electrical smoking system with the cigarette in a partially unassembled condition.

[0015] FIG. 2 illustrates the electrically heated cigarette shown in FIG. 1 in the assembled condition with one end of the cigarette contacting a stop piece of an electrically operated lighter of the electrical smoking system.

15 [0016] FIG. 3 illustrates another preferred embodiment of an electrically heated cigarette for use in an electrical smoking system with the cigarette in a partially unassembled condition.

20 [0017] FIG. 4 illustrates a preferred embodiment of an electrical smoking system with an electrically heated cigarette inserted into the electrically operated lighter.

[0018] FIG. 5 illustrates the electrical smoking system shown in FIG. 4 with the cigarette withdrawn from the lighter.

[0019] FIG. 6 illustrates a heater fixture of the electrical smoking system.

-6-

## DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0020] An electrically heated cigarette includes one or more sorbents and at least one flavoring for affecting flavor, taste, and/or aroma of tobacco smoke. In a preferred embodiment, the flavoring is incorporated in the cigarette in a flavoring-release additive, which preferably minimizes the release and/or migration of the flavoring in the cigarette prior to smoking. Preferably, the flavoring is released from the flavoring-release additive in a controlled manner during smoking of the cigarette. The flavoring-release additive enables the flavoring to enhance subjective characteristics of the cigarette while avoiding an adverse impact on the effectiveness of the sorbent in removing selected gas-phase constituents from mainstream smoke.

[0021] In a preferred embodiment of the electrically heated cigarette, the flavoring is released in the cigarette upon the flavoring-release additive being heated to at least a minimum temperature (flavoring release temperature), which occurs when a smoker draws mainstream smoke through the cigarette.

[0022] It has been determined that different regions of the electrically heated cigarette reach different temperatures when a smoker draws on the cigarette. In a preferred embodiment, different flavoring-release additives are selectively disposed at two or more locations in the electrically heated cigarette that respectively reach at least the minimum temperature at which the flavoring is released from the flavoring-release additive disposed at that location. By selectively locating one or more flavoring-release additives in the cigarette, the cigarette can provide efficient, controlled release of the flavoring during smoking.

[0023] The flavoring-release additive can have various constructions and compositions and can be located at one or more locations, and/or incorporated in one or more components of the electrically heated cigarette. The flavoring-release additives can be designed to have different associated flavoring release



-7-

temperatures. Accordingly, the flavoring-release additives can be incorporated in the electrically heated cigarette at locations that are most suitable for providing efficient release of the flavoring from the particular flavoring-release additive.

[0024] The electrically heated cigarette can comprise one or more sorbents  
5 capable of removing selected gas-phase constituents from mainstream smoke. By providing the flavoring in the flavoring-release additive that preferably minimizes the release and/or migration of the flavoring in the cigarette until the flavoring-release additive reaches at least the minimum temperature, the flavoring is preferably substantially prevented from deactivating the sorbent. Thus, the ability  
10 of the sorbent to remove selected gas-phase constituents from mainstream tobacco smoke can be maintained. Preferably, the flavoring-release additive enables the flavoring to be effectively delivered to a smoker in a controlled manner.

[0025] As used herein, the term "sorption" denotes filtration by adsorption and/or absorption. Sorption is intended to encompass interactions on the outer  
15 surface of the sorbent, as well as interactions within the pores and channels of the sorbent. In other words, a "sorbent" is a substance that has the ability to condense or hold molecules of other substances on its surface, and/or the ability to take up other substances, i.e., through penetration of the other substances into its inner structure, or into its pores. The term "sorbent" as used herein refers to either an  
20 adsorbent, an absorbent, or a substance that can function as both an adsorbent and an absorbent.

[0026] As used herein, the term "remove" refers to adsorption and/or absorption of at least some portion of a component of mainstream tobacco smoke.

[0027] The term "mainstream smoke" includes the mixture of gases passing  
25 down the tobacco rod and issuing through the filter end, i.e., the amount of smoke issuing or drawn from the mouth end of a cigarette during smoking of the

-8-

cigarette. The mainstream smoke contains air that is drawn in through the heated region of the cigarette and through the paper wrapper.

[0028] The term "molecular sieve" as used herein refers to a porous structure comprised of an inorganic material and/or organic material. Molecular sieves  
5 include natural and synthetic materials. Molecular sieves can sorb molecules of certain dimensions, while rejecting molecules having larger dimensions.

[0029] FIGS. 1 and 2 illustrate a preferred embodiment of the electrically heated cigarette 23. However, it should be understood that the electrically heated  
10 cigarette can have other configurations suitable for smoking in an electrically powered lighter. The electrically heated cigarette 23 comprises a tobacco rod 60 and a filter tipping 62 joined together by tipping paper 64. The tobacco rod 60 preferably includes a tobacco web or "mat" 66 folded into a tubular form about a free-flow filter 74 at one end and a tobacco plug 80 at the other end.

[0030] An over wrap 71 surrounds the tobacco-containing mat 66 and is held  
15 together along a longitudinal seam. The over wrap 71 retains the mat 66 in a wrapped condition about the free-flow filter 74 and tobacco plug 80.

[0031] The mat 66 preferably comprises a base web 68 and a layer of tobacco material 70. The tobacco material 70 can be located along the inside surface or the  
20 outside surface of the base web 68. At the tipped end of the tobacco rod 60, the mat 66 and the over wrap 71 are wrapped about the free-flow filter plug 74. Preferably, the tobacco plug 80 comprises a relatively short tobacco column 82 of cut filler tobacco, which is retained by a surrounding inner wrap 84.

[0032] A void 90 is between the free-flow filter 74 and the tobacco plug 80.  
25 The void 90 is an unfilled portion of the tobacco rod 60 and is in fluid communication with the tipping 62 through the free flow filter 74.

[0033] The tipping 62 preferably comprises a free-flow filter 92 located adjacent the tobacco rod 60 and a mouthpiece filter plug 94 at the distal end of the tipping

-9-

62 from the tobacco rod 60. Preferably, the free-flow filter 92 is tubular and transmits air with very low pressure drop. The mouthpiece filter plug 94 closes off the free end of the tipping 62.

5 [0034] The cigarette 23 optionally includes at least one row of perforations 12 adjacent the free end 15 of the cigarette 23. The perforations can be formed as slits 17, which preferably extend through the over wrap 71, the mat 66 and the inner wrap 84.

10 [0035] To further improve delivery, at least one additional row of perforations 14 comprising slits 17 can optionally be formed at a location along the tobacco plug 80. The perforations 12 or 14 may comprise a single row or a dual row of slits 17. The number and extent of the slits 17 can be selected to control the resistance to draw (RTD) along the side walls of the cigarettes 23 and the delivery.

15 [0036] Optional holes 16 provided in the mat 66 are covered by the over wrap 71. The perforations 12, 14 can be used to approximate desired delivery levels for the cigarette 23, with the holes 16 being used to adjust delivery with a lesser effect on the RTD.

20 [0037] The cigarette 23 preferably has a substantially constant diameter along its length. The diameter of the cigarette 23, like more traditional cigarettes, is preferably between about 7.5 mm to 8.5 mm so that the electrical smoking system 21 provides a smoker with a familiar "mouth feel" during smoking.

[0038] The tobacco column 82 preferably comprises cut filler of a typical blend of tobaccos, such as blends comprising bright, Burley, and Oriental tobaccos together with, optionally, reconstituted tobaccos and other blend components, including traditional cigarette flavors.

25 [0039] The free-flow filter 92 and the mouthpiece filter plug 94 are preferably joined together as a combined plug with a plug wrap 101. The plug wrap 101 is

-10-

preferably a porous, low-weight plug wrap. The combined plug is attached to the tobacco rod 60 by the tipping paper 64.

[0040] As described above, the electrically heated cigarette 23 can comprise one or more sorbents that remove gas-phase constituents of tobacco smoke. The sorbent can comprise one or more porous materials through which tobacco smoke can flow. In a preferred embodiment, the sorbent is activated carbon. For example, the sorbent can comprise activated carbon granules located in a void in the filter, or activated carbon particles loaded on fibrous material or paper. The activated carbon can be in various forms including particles, fibers, beads, and the like. The activated carbon can have different porosity characteristics, such as a selected pore size and total pore volume.

[0041] In another preferred embodiment, the sorbent is one or more suitable molecular sieve sorbent materials. Molecular sieve sorbents that may be used in the electrically heated cigarette 23 include, but are not limited to, one or more of the zeolites, mesoporous silicates, alumino phosphates, mesoporous aluminosilicates, and other related porous materials, such as mixed oxide gels, which may optionally further comprise inorganic or organic ions and/or metals. See, for example, commonly-owned International Publication No. WO 01/80973, which is incorporated herein by reference in its entirety.

[0042] In a preferred embodiment, the sorbent is one or more zeolites. Zeolites include crystalline aluminosilicates having pores, such as channels and/or cavities of uniform, molecular sized dimensions. There are many known unique zeolite structures having different sized and shaped pores, which can significantly affect the properties of these materials with regard to sorption and separation processes. Molecules can be separated by zeolites by size and shape effects related to the possible orientation of the molecules in the pores, and/or by differences in strength of sorption. One or more zeolites having pores larger than one or more selected

-11-

gas phase components of a gas that is desired to be filtered can be used in the electrically heated cigarette 23, such that only selected molecules that are small enough to pass through the pores of the molecular sieve material are able to enter the cavities and be sorbed on the zeolite.

5 [0043] The zeolite can be, but is not limited to, one or more of zeolite A; zeolite X; zeolite Y; zeolite K-G; zeolite ZK-5; zeolite BETA; zeolite ZK-4 and zeolite ZSM-5. In a preferred embodiment, zeolite ZSM-5 and/or zeolite BETA is used. ZSM-5 is in the MFI structural classification family and represented by the crystal chemical data  $[\text{Na}_n(\text{Al}_n\text{Si}_{96-n}\text{O}_{192}) \sim 16\text{H}_2\text{O}]$ , with  $n < 27$ , orthorhombic, Pnma],  
10 while zeolite BETA is in the BEA structural classification family and represented by the crystal chemical data  $[\text{Na}_7(\text{Al}_7\text{Si}_{57}\text{O}_{128})]$  tetragonal, P4<sub>1</sub>22]. These two zeolites are thermally stable at temperatures up to about 800°C, allowing them to be incorporated in cigarette filters and/or the tobacco rod of the electrically heated cigarette 23.

15 [0044] In another preferred embodiment, the sorbent incorporated in the electrically heated cigarette 23 has a composite composition. In such embodiment, the sorbent comprises, for example, activated carbon and one or more molecular sieve materials, such as those described above. For example, sorbent fibers can be impregnated with at least one sorbent.

20 [0045] Microporous, mesoporous, and/or macroporous molecular sieves may be used in the electrically heated cigarette 23, depending on the selected component(s) desired to be removed from mainstream tobacco smoke.

[0046] The sorbent can be incorporated in one or more locations of the electrically heated cigarette 23. For example, the sorbent can be placed in the  
25 passageway of the tubular free-flow filter 74, in the free-flow filter 92, and/or in the void space 90. The sorbent can additionally or alternatively be incorporated in the tobacco plug 80.

-12-

[0047] FIG. 3 shows another preferred embodiment of an electrically heated cigarette 23 including a filter 150. The filter 150 comprises a sorbent in the form of oriented fibers 152 and a sleeve 154, such as paper, surrounding the fibers. The sorbent can be, for example, one or more of activated carbon, silica gel, zeolite, and other molecular sieves in fibrous forms. The sorbents can be surface modified materials, for example, surface modified silica gel, such as amino propyl silyl (APS) silica gel. Sorbent mixtures can provide different filtration characteristics to achieve a targeted filtered mainstream smoke composition.

[0048] Alternatively, the fibers 152 can comprise one or more sorbent materials, such as carbon, silica, zeolite and the like, impregnated in microcavity fibers, such as TRIAD™ micro-cavity fiber, as disclosed in commonly-owned International Publication No. WO 01/80973. In a preferred embodiment, the fibers are shaped microcavity fibers impregnated with particles of one or more sorbent materials, or alternatively continuous activated carbon fibers. The fibers preferably have a diameter of from about 10 microns to about 100 microns. The fibers can have a length of from about 10 microns to about 200 microns, for example.

[0049] In another preferred embodiment, the fibers are bundles of non-continuous fibers, which are preferably oriented parallel to the direction of mainstream smoke flow through the electrically heated cigarette.

[0050] The filters 150 including fibers 152 can be formed, for example, by stretching a bundle of non-crimped sorbent fiber material, preferably having a controlled total and per filament denier, through a pre-formed or in-situ formed sleeve 154 during the filter making process. The formed filter can be sized by cutting to a desired length. For example, the filters can have a length of from about 5 mm to about 30 mm.

[0051] The filter 150 including fibers 152 can be incorporated in the electrically heated cigarette at one or more desired locations. Referring also to FIGS. 1 and 2,

-13-

in a preferred embodiment, the filter 150 can be substituted for the entire free-flow filter 92. In another preferred embodiment, the free-flow filter 150 can be substituted for a portion of the free-flow filter 92. The filter 150 can be in contact with (i.e., abut) the free-flow filter 74, positioned between the free-flow filter 74 and the mouthpiece filter plug 94, or in contact with (i.e., abut) the mouthpiece filter plug 94. The filter 150 preferably has a diameter substantially equal to that of the outer diameter of the free-flow filter 92 to minimize by-pass of smoke during the filtration process.

[0052] The fibrous sorbents preferably have a high loft with a suitable packing density and fiber length such that parallel pathways are created between fibers. Such structure can effectively remove significant amounts of selected gas-phase constituents, such as formaldehyde and/or acrolein, while preferably removing only a minimal amount of particulate matter from the smoke, thereby achieving a significant reduction of the selected gas-phase constituents, while not significantly affecting the total particulate matter (TPM) in the gas. A sufficiently low packing density and a sufficiently short fiber length are preferred to achieve such filtration performance.

[0053] The amount of sorbent used in preferred embodiments of the electrically heated cigarette 23 depends on the amount of selected gas-phase constituents in the tobacco smoke and the amount of the constituents that is desired to be removed from the tobacco smoke.

[0054] As described above, the electrically heated cigarette 23 also comprises at least one flavoring-release additive. The flavoring can be, for example, one or more flavorings including, but not limited to, menthol, mint, such as peppermint and spearmint, chocolate, licorice, citrus and other fruit flavors, gamma octalactone, vanillin, ethyl vanillin, breath freshener flavors, spice flavors, such as cinnamon, methyl salicylate, linalool, bergamot oil, geranium oil, lemon oil,

-14-

ginger oil, and tobacco flavor. In a preferred embodiment, the flavoring is menthol and optionally at least one mint flavoring.

[0055] As described above, the flavoring-release additive can have different structures and compositions in the electrically heated cigarette. In one preferred  
5 embodiment, the flavoring-release additive is in the form of beads. The beads preferably encapsulate the flavoring and provide for controlled release of the flavoring in the cigarette during puff cycles.

[0056] The beads preferably comprise at least one encapsulating material and at least one flavoring. The encapsulating material preferably comprises a binder,  
10 which can be, for example, one or more of palm oil, konjac gum, xylitol, zein, hydroxypropylcellulose, sorbitol, maltitol, and hydroxypropylmethylcellulose. Other materials known in the art that can improve the bead-forming characteristics of the encapsulating material or enhance its stability can optionally also be added  
15 in the beads. In a preferred embodiment, the beads have a substantially homogenous composition in which flavoring is substantially uniformly distributed. By such structure, the flavoring can be released from the beads in a more uniform manner during smoking.

[0057] Depending on the composition of the beads, the minimum temperature at which the beads release the flavoring can be adjusted. Beads comprising one or  
20 more of the above-described binders preferably have a minimum temperature at which the flavoring is released of at least about 40°C, such as about 40°C to about 150°C. The beads protect the flavoring from exposure to undesired substances in the atmosphere (e.g., ambient air, inside a package) and undesired substances in the cigarette, and preferably minimize release and/or migration of the flavoring  
25 until the flavoring-release additive is heated to a sufficiently high temperature during smoking of the cigarette. Consequently, the flavoring is preferably substantially prevented from migrating in the cigarette, reacting with other



-15-

substances in the cigarette or with the environment, and deactivating sorbent present in the cigarette.

5 [0058] The beads can have any desired shape, such as different regular and irregular shapes, including round, square, rectangular, oval, other polygonal shapes, cylindrical, fibrous, and the like. The beads can have various sizes. Preferably, the beads are microbeads having a maximum particle size of less than about 25 microns, and more preferably less than about 1 micron. Decreasing the size of the beads can provide a more homogenous and controlled release of flavoring by providing increased surface area of the beads.

10 [0059] The beads can be manufactured by any suitable process that produces beads having the desired structure, composition, and size. For example, the beads can be manufactured by extrusion, spray drying, coating, or other suitable processes. In a preferred embodiment, the beads are formed by forming a solution, dispersion or emulsion containing a binder, flavoring and optional  
15 additives to form beads, which can be isolated and dried. Processes for preparing beads containing an active ingredient, such as a flavor, are disclosed in U.S. Patent No. 6,325,859, which is incorporated herein by reference in its entirety.

[0060] The electrically heated cigarette 23 preferably comprises an amount of the beads that provides a desired amount of the flavoring in the cigarette. In a  
20 preferred embodiment, the electrically heated cigarette comprises, based on the total weight of tobacco in the cigarette, up to about 20%, and more preferably about 10% to about 15%, of the beads. For example, a cigarette containing 100 mg of tobacco preferably contains up to about 20 mg of beads. The beads can preferably comprise up to about 20% of flavoring. The cigarette can comprise,  
25 for example, from about 1 mg to about 15 mg of flavoring.

[0061] In a preferred embodiment, the beads are disposed in at least one location in the electrically heated cigarette 23 that reaches at least the minimum

-16-

temperature at which the flavoring is released from the beads and into the cigarette during smoking. For example, the beads can be disposed in the tobacco rod 60, in the void 90 between the tobacco plug 80 and the free-flow filter 74, on one or more surfaces of the free-flow filter 74, on or in the mat 66, and/or on or in the inner wrap 84 surrounding the tobacco plug 80.

[0062] In another preferred embodiment, different bead compositions having two or more different minimum flavoring-release temperatures can be incorporated at two or more locations in an electrically heated cigarette that reaches different temperatures at such locations during smoking. For example, beads having a first flavoring release temperature can be located at a first location in the cigarette that reaches the first flavoring-release temperature, and beads having a second flavoring-release temperature higher than the first flavoring-release temperature can be located at a second location in the cigarette that reaches the second flavoring-release temperature. For example, the two flavoring release temperatures can vary by up to about 100°C. For example, these two temperatures can vary by up to about 10°C, 20°C, 30°C, 40°C, 50°C, 60°C, 70°C, 80°C, 90°C, or 100°C.

[0063] In another preferred embodiment, the flavoring-release additive includes a film. The film preferably encapsulates the flavoring and enables the controlled temperature release of the flavoring in the cigarette during smoking. In a preferred embodiment, the film comprises by weight up to 20%, more preferably about 10% to about 15%, of the flavoring. In a preferred embodiment, the film encapsulates menthol and optionally also mint.

[0064] The film-type flavoring-release additive preferably comprises at least one encapsulating material and at least one flavoring. The encapsulating material preferably comprises a binder, which can be, for example, one or more of carraghenan, gelatin, agar, gellan gum, gum arabic, guar gum, xanthum gum, and

-17-

pectin. Other materials known in the art that can improve the film-forming characteristics of the encapsulating material or enhance its stability can optionally be added to the film. In a preferred embodiment, the film has a substantially homogenous composition in which flavoring is substantially uniformly distributed. By such structure, the flavoring can be released from the film in a more desired manner during smoking. The film encapsulating material provides a barrier to the release of the flavoring.

[0065] Depending on the composition of the film, the minimum temperature at which the film releases the flavoring can be adjusted/selected. A film comprising one or more of the above-described binders preferably has a minimum temperature at which the flavoring is released of at least about 50°C, such as up to about 120°C. The film protects the flavoring from exposure to undesired substances in the cigarette and atmosphere and substantially prevents the flavoring from being released until the film is heated to the flavoring release temperature during smoking of the cigarette.

[0066] The film can be applied to one or more components of the electrically heated cigarette as a liquid coating, which is dried to a film. The dimensions of the dried film are not limited. Preferably, the dried film has a maximum thickness of about 50 microns to about 150 microns, and more preferably about 75 microns.

[0067] The film can be manufactured by any suitable process that produces a film having the desired structure, composition, and dimensions. For example, the film can be applied by a coating process, such as spray coating, a dipping process, electrostatic deposition, printing wheel application, gravure printing, ink jet application, and the like. In a preferred embodiment, an emulsion, suspension or slurry comprising the binder, flavoring, and optional additives is prepared and then applied as a coating to one or more selected surfaces of one or more selected components of the electrically heated cigarette. The coating is preferably dried to

-18-

remove water and/or other solvents and form a solid film having desired dimensions. Exemplary processes that can be used to prepare the films are described in U.S. Patents Nos. 3,006,347 and commonly-owned 4,715,390, each of which is incorporated herein by reference in its entirety.

5 [0068] The electrically heated cigarette 23 preferably comprises an amount of the film that releases a desired amount of the flavoring during smoking of the cigarette. In a preferred embodiment, the electrically heated cigarette comprises, based on the total weight of tobacco in the cigarette to which the film is applied, up to about 20%, and more preferably about 10% to about 15%, of the film. For  
10 example, if the film is applied to the mat, the weight of tobacco contained in the mat preferably is the weight basis for the amount of the film. If the film is applied to the mat and to the tobacco plug, the total weight of tobacco contained in the mat and the tobacco plug preferably is the weight basis for the amount of film applied in the cigarette. Preferably, the weight of tobacco contained in the mat is the  
15 weight basis for the amount of film applied to the mat, and the weight of tobacco contained in the tobacco plug is the weight basis for the amount of film applied to the tobacco plug. In a preferred embodiment, the cigarette can comprise from about 1 mg to about 15 mg of flavoring.

[0069] In a preferred embodiment, the film is disposed in at least one location in  
20 the electrically heated cigarette 23 that reaches at least the flavoring release temperature. For example, the film can be disposed on the tobacco plug 80, on the inner wrap 84 surrounding the tobacco plug 80, on the mat 66, and/or on the over wrap 71 surrounding the mat. When the film is disposed on the inner wrap 84 and/or over wrap 71, the weight of the inner wrap 84 and/or over wrap 71 is  
25 the weight basis for the amount of the film. In another preferred embodiment, the film can be preformed, shredded and incorporated in the tobacco plug 80, and/or other selected locations that reach the flavoring release temperature.

-19-

[0070] In another preferred embodiment, different flavored films having two or more different minimum flavoring-release temperatures can be incorporated at different locations in an electrically heated cigarette, where during smoking of the cigarette, the temperatures at the different locations exceed the minimum release temperatures of the different films.

[0071] In another preferred embodiment, the flavoring-release additive is an inclusion complex. The inclusion complex comprises a "host molecule," and the flavoring is the "guest molecule" in the inclusion complex. The inclusion complex provides for controlled release of the flavoring in the cigarette during smoking.

In a preferred embodiment, the flavoring is a lipophilic organic flavoring, which preferably concentrates within a hydrophobic cavity of the host molecule. Suitable flavorings include, but are not limited to, menthol, mint, such as peppermint and spearmint, chocolate, licorice, citrus and other fruit flavors, gamma octalactone, vanillin, ethyl vanillin, breath freshener flavors, spice flavors, such as cinnamon, methyl salicylate, linalool, bergamot oil, geranium oil, lemon oil, ginger oil, and tobacco flavor. In a preferred embodiment, the flavoring includes vanillin and gamma octalactone. In a preferred embodiment, the inclusion complex comprises by weight up to about 20%, more preferably from about 10% to about 15%, of the flavoring.

[0072] The host molecule of the inclusion complex is preferably a cyclodextrin. Cyclodextrins are cyclic oligosaccharides including glucopyranose subunits, as described, for example, in U.S. Patents No. 3,426,011 and commonly-owned U.S. Patent No. 5,144,964, each of which is incorporated herein by reference in its entirety. The inclusion complex is formed when a flavoring material is mixed with a selected cyclodextrin in solution. The flavoring resides inside the cyclodextrin ring structure. The cyclodextrins and flavoring are typically co-precipitated, filtered, and dried.

-20-

[0073] Alpha-cyclodextrin, beta-cyclodextrin and gamma-cyclodextrin include six, seven and eight glucopyranose subunits, respectively. In a preferred embodiment, the inclusion complex comprises beta-cyclodextrin, which can desirably accommodate a wide variety of guest molecules and is readily available.

5   Beta-cyclodextrin has a ring structure of the linked subunits with a three-dimensional torus configuration including a hydrophobic cavity with a 7.5 Å diameter and hydrophilic upper and lower edges.

[0074] The minimum temperature at which the inclusion complex comprising a cyclodextrin releases the flavoring is preferably at least about 60°C, such as from  
10   about 60°C to about 125°C. By incorporating the flavoring in the inclusion complex, the flavoring can be protected from exposure to undesired substances in the cigarette and the atmosphere release and/or migration of the flavoring is preferably minimized until the flavoring-release additive is heated to the flavoring release temperature during smoking of the cigarette.

15   [0075] The inclusion complex is preferably in powder form. The powder preferably has maximum size of less than about 200 microns.

[0076] The inclusion complex can be made by forming an aqueous solution of beta-cyclodextrin and the flavoring. The inclusion complex can be recovered from the solution in powder form. However, the solution can be applied directly to one  
20   or more selected locations of one or more components of the electrically heated cigarette by any suitable process. The inclusion complex powder can alternatively be used to form a solution or a suspension. The inclusion complex can be applied by a coating process, such as slurry coating, spraying, a dipping process, electrostatic deposition, printing wheel application, gravure printing, ink jet  
25   application, and the like. In a preferred embodiment, a solution, suspension or slurry comprising the cyclodextrin and flavoring is prepared and applied as a coating to selected surfaces of selected components of the electrically heated

-21-

cigarette. Exemplary processes that can be used to apply the inclusion complex in the electrically heated cigarette are described in commonly-owned U.S. Patent No. 5,144,964, which is incorporated herein by reference in its entirety.

5 [0077] The electrically heated cigarette 23 preferably comprises an amount of the inclusion complex that provides a desired amount of the flavoring in the cigarette. In a preferred embodiment, the electrically heated cigarette comprises, based on the weight of the over wrap or mat, up to about 15%, and more preferably less than about 8%, of the inclusion complex. For example, if the inclusion complex is applied to the mat, then the weight of the mat preferably is  
10 the weight basis for the amount of the inclusion complex applied to the mat. If the inclusion complex is applied to the mat and the over wrap, then the total weight of the mat and the over wrap preferably is the weight basis for the amount of the inclusion complex applied to the mat and the over wrap. The weight percent of the inclusion complex that is applied to the mat and/or over wrap can be the same  
15 or different. In a preferred embodiment, the cigarette comprises from about 1 mg to about 50 mg of flavoring.

[0078] In a preferred embodiment, the inclusion complex is disposed in at least one location in the electrically heated cigarette 23 that reaches at least the minimum temperature at which the flavoring is released from the inclusion  
20 complex in the cigarette during smoking. For example, the inclusion complex can be disposed on the inner wrap 84, mat 66, and/or the over wrap 71.

[0079] In another preferred embodiment, the electrically heated cigarette comprises two or more different types of flavoring-release additives, for example, a bead and a film and/or an inclusion complex, with each flavoring-release additive  
25 having a different flavoring release temperature. The different flavoring-release additives can be incorporated at two or more locations in the same electrically

-22-

heated cigarette that reach different temperatures during smoking in order to provide further controlled release of the flavoring during smoking.

[0080] FIGS. 4 and 5 illustrate a preferred embodiment of an electrical smoking system in which preferred embodiments of the electrically heated cigarette can be used. However, it should be understood that preferred embodiments of the electrically heated cigarette can be used in electrical smoking systems having other constructions, such as those having different electrically powered lighter constructions. The electrical smoking system 21 includes an electrically heated cigarette 23 and a reusable lighter 25. The cigarette 23 is constructed to be inserted into and removed from a cigarette receiver 27, which is open at a front end portion 29 of the lighter 25. Once the cigarette 23 is inserted, the smoking system 21 is used in a similar manner as a more traditional cigarette, but without lighting or smoldering of the cigarette 23. The cigarette 23 is discarded after smoking.

[0081] Preferably, each cigarette 23 provides a total of at least eight puffs (puff cycles) per smoke. However, the cigarette 23 can be constructed to provide a lesser or greater total number of available puffs.

[0082] The lighter 25 includes a housing 31 having front and rear housing portions 33 and 35, respectively. A power source 35a, such as one or more batteries, is located within the rear housing portion 35 and supplies energy to a heater fixture 39. The heater fixture 39 includes a plurality of electrically resistive, heating elements 37 (FIG. 6). The heating elements 37 are arranged within the front housing portion 33 to slidably receive the cigarette 23. A stop 183 located in the heater fixture 39 defines a terminal end of the cigarette receiver 27 (FIG. 2).



-23-

[0083] Control circuitry 41 in the front housing portion 33 selectively establishes electrical communication between the power source 35a and one or more of the heating elements 37 during each puff cycle.

5 [0084] The rear housing portion 35 of the housing 31 is constructed to be opened and closed to facilitate replacement of the power source 35a. Preferably, the front housing portion 33 is removably attached to the rear housing portion 35 by mechanical engagement.

[0085] Referring to FIG. 5, in a preferred embodiment, the control circuitry 41 is activated by a puff-actuated sensor 45, which is sensitive to either changes in  
10 pressure or changes in the rate of air flow that occur upon initiation of a draw on the cigarette 23 by a smoker. The puff-actuated sensor 45 is preferably located within the front housing portion 33 of the lighter 25 and communicates with a space inside the heater fixture 39 via a port 45a extending through a side wall portion 182 of the heater fixture 39. Once actuated by the sensor 45, the control  
15 circuitry 41 directs electric current to an appropriate one of the heating elements 37.

[0086] In a preferred embodiment, an indicator 51 is provided at a location along the exterior of the lighter 25 to visually indicate the number of puffs remaining in a cigarette 23, or other selected information. The indicator 51  
20 preferably includes a liquid crystal display. In a preferred embodiment, the indicator 51 displays a selected image when a cigarette detector 57 detects the presence of a cigarette in the heater fixture 39. The detector 57 can comprise any arrangement that senses the presence of an electrically heated cigarette. For example, the detector can comprise an inductive coil 1102 adjacent the cigarette  
25 receiver 27 of the heater fixture 39 and electric leads 1104 that communicate the coil 1102 with an oscillator circuit within the control circuitry 41. In such case, the cigarette 23 can include a metallic element (not shown), which can affect

-24-

inductance of the coil winding 1102 such that whenever a suitable cigarette 23 is inserted into the receiver 27, the detector 57 generates a signal to the circuitry 41 indicating the cigarette is present. The control circuitry 41 provides a signal to the indicator 51. When the cigarette 23 is removed from the lighter 25, the cigarette  
5 detector 57 no longer detects the presence of a cigarette 23 and the indicator 51 is turned off.

[0087] The heater fixture 39 supports an inserted cigarette 23 in a fixed relation to the heating elements 37 such that the heating elements 37 are positioned alongside the cigarette 23 at approximately the same location for each newly  
10 inserted cigarette 23. In a preferred embodiment, the heater fixture 39 includes eight mutually parallel heater elements 37, which are disposed concentrically about the axis of symmetry of the cigarette receiver 27. The location where each heating element 37 touches a fully inserted cigarette 23 is referred to herein as the heater footprint or char zone 42.

15 [0088] As shown in FIG. 6, the heating elements 37 preferably each include at least first and second serpentine, elongate members 53a and 53b adjoined at a tip 54. The heater portions 53a, 53b and 54 form a heater blade 120. The tips 54 are adjacent the opening 55 of the cigarette receiver 27. The opposite ends 56a and 56b of each heating element 37 are electrically connected to the opposite poles of  
20 the power source 35a as selectively established by the controller 41. An electrical pathway through each heating element 37 is established, respectively, through a terminal pin 104, a connection 121 between the pin 104 and a free end portion 56a of one of the serpentine members 53a, through at least a portion of the tip 54 to the other serpentine member 53b and its end portion 56b. Preferably, a connection  
25 ring 110 provides a common electrical connection to each of the end portions 56b. In a preferred embodiment, the ring 110 is connected to the positive terminal of

-25-

the power source 35a through a connection 123 between the ring 110 and a pin 105.

[0089] Preferably, the heating elements 37 are individually energized by the power source 35a under the control of the control circuitry 41 to heat the cigarette 23 preferably eight times at spaced locations about the periphery of the cigarette 23. The heating renders eight puffs from the cigarette 23, as is commonly achieved with the smoking of a more traditional cigarette. It may be preferred to activate more than one heating element simultaneously for one or more or all of the puffs.

10 [0090] The heater fixture 39 includes an air inlet port 1200 through which air is drawn into the lighter. A pressure drop is induced upon the air entering the lighter such that the puff sensor 45 is operative to recognize initiation of a puff. The range of pressure drop induced is selected such that it is within the range of pressure drop detectable by the pressure sensor 45.

15 [0091] The length of the tobacco plug 80 and its relative position along the tobacco rod 60 is preferably selected based on the construction and location of the heating elements 37 of the electrical smoking system 21. When a cigarette 23 is properly positioned against a stop 182 (FIG. 2) within the lighter of the electrical smoking system, a portion of each heating element contacts the tobacco rod 60.

20 This region of contact is referred to as a heater footprint 95, which is that region of the tobacco rod 60 where the heating element 37 is expected to reach a temperature high enough to allow smoking of the cigarette without combustion of the cigarette paper, mat or tobacco. The heater foot print 95 can consistently locate along the tobacco rod 60 at the same predetermined distance 96 from the  
25 free end 78 of the tobacco rod 60 for every cigarette 23 that is fully inserted into the lighter 25.

-26-

[0092] Preferably, the length of the tobacco plug 80 of the cigarette 23, the length of the heater footprint 95, and the distance between the heater footprint 95 and the stop 182 are selected such that the heater footprint 95 extends beyond the tobacco plug 80 and superposes a portion of the void 91 by a distance 98. The distance 98 is also referred to as the "heater-void overlap" 98. The distance over which the remainder of the heater footprint 95 superposes the tobacco plug 80 is referred to as the "heater-filler overlap" 99.

[0093] The length of the void 91, tobacco plug 80, and the distribution of the perforation holes 263 may be adjusted to adjust the smoking characteristics of the cigarette 23, including adjustments in its taste, draw and delivery. The pattern of holes 263, the length of the void 90 and the amount of heater-filler overlap 99 (and heater-void overlap 98) may also be manipulated to adjust the immediacy of response, to promote consistency in delivery.

[0094] Electrically heated cigarettes according to preferred embodiments can provide advantages. By encapsulating one or more added flavorings, especially volatile flavoring, the flavoring(s) can be retained in the cigarette until it is smoked. In addition, the flavoring is preferably temperature released in a controlled manner during smoking, thereby providing the smoker with an enhanced subjective characteristic of the cigarette. As the flavoring can be retained in the flavoring-release additive until the cigarette is smoked, deactivation of the sorbent in the cigarette is preferably minimized. Consequently, the sorbent maintains its ability to remove selected gas phase constituents from mainstream smoke.

[0095] The invention may be embodied in other specific forms without departing from the spirit of the invention. Thus, while the invention has been illustrated and described in accordance with various preferred embodiments, it is recognized that

-27-

variations and changes may be made therein without departing from the invention as set forth in the claims.

-28-

**What is claimed is:**

1. An electrically heated cigarette for an electrical smoking system,  
comprising:  
at least one sorbent; and  
5 a flavoring-release additive including at least one flavoring releasable in the  
electrically heated cigarette upon the flavoring-release additive being heated to at  
least a minimum temperature.
2. The electrically heated cigarette of Claim 1, wherein the sorbent is  
10 activated carbon.
3. The electrically heated cigarette of Claim 1, wherein the sorbent is  
zeolite.
- 15 4. The electrically heated cigarette of Claim 1, wherein the flavoring is  
(i) menthol, or (ii) vanillin and gamma octalactone.
5. The electrically heated cigarette of Claim 1, wherein the flavoring is  
at least one flavoring selected from the group consisting of menthol, mint,  
20 chocolate, licorice, fruit flavors, gamma octalactone, vanillin, ethyl vanillin,  
breath freshener flavors, spice flavors, methyl salicylate, linalool, bergamot oil,  
geranium oil, lemon oil, ginger oil, and tobacco flavor.
6. The electrically heated cigarette of Claim 1, wherein the flavoring-  
25 release additive is in the form of beads.

-29-

7. The electrically heated cigarette of Claim 6, wherein the beads comprise a binder selected from the group consisting of palm oil, konjac gum, hydroxypropylcellulose, xylitol, zein, sorbitol, maltitol, and hydroxypropylmethylcellulose.

5

8. The electrically heated cigarette of Claim 6, wherein the beads have a maximum particle size of less than about 25 microns.

10

9. The electrically heated cigarette of Claim 8, wherein the beads have a maximum particle size of less than about 1 micron.

15

10. The electrically heated cigarette of Claim 6, which comprises, based on the total weight of tobacco in the electrically heated cigarette, up to about 20% by weight of the beads.

11. The electrically heated cigarette of Claim 6, wherein the beads comprise by weight up to about 20% of the flavoring.

20

12. The electrically heated cigarette of Claim 6, wherein the minimum temperature is about 40°C and the beads are disposed in at least one location in the electrically heated cigarette that reaches at least about 40°C during smoking of the cigarette.

25

13. The electrically heated cigarette of Claim 6, wherein the beads are disposed in a tobacco rod, in a void between a tobacco plug and a free-flow filter, on a free-flow filter, on a tobacco-containing mat, and/or on an inner wrap surrounding the tobacco plug.

-30-

14. The electrically heated cigarette of Claim 1, wherein the flavoring-release additive is a film.

15. The electrically heated cigarette of Claim 14, wherein the film  
5 comprises a binder selected from the group consisting of carraghenan, gelatin, agar, gellan gum, gum arabic, guar gum, xanthum gum, and pectin.

16. The electrically heated cigarette of Claim 14, wherein the film has a  
10 thickness of less than about 150 microns.

17. The electrically heated cigarette of Claim 14, which comprises,  
based on the total weight of tobacco in the electrically heated cigarette, up to about  
20% by weight of the film.

18. The electrically heated cigarette of Claim 14, wherein the film  
15 comprises by weight up to about 20% of the flavoring.

19. The electrically heated cigarette of Claim 14, wherein the film is in  
shredded form.  
20

20. The electrically heated cigarette of Claim 14, wherein the minimum  
temperature is about 50°C, and the film is disposed in at least one location in the  
electrically heated cigarette that reaches at least about 50°C during smoking of the  
cigarette.  
25



-31-

21. The electrically heated cigarette of Claim 14, wherein the film is disposed in a tobacco plug, on an inner wrap surrounding the tobacco plug, on a tobacco-containing mat, and/or on an over wrap surrounding the mat.

5 22. The electrically heated cigarette of Claim 1, wherein the flavoring-release additive is an inclusion complex which includes a host molecule and the flavoring is a guest molecule in the inclusion complex.

23. The electrically heated cigarette of Claim 22, wherein the host  
10 molecule is beta-cyclodextrin.

24. The electrically heated cigarette of Claim 22, which comprises, based on the weight of an over wrap and/or mat, less than about 15% by weight of the inclusion complex.

15 25. The electrically heated cigarette of Claim 22, wherein the inclusion complex comprises up to about 20% of the flavoring.

26. The electrically heated cigarette of Claim 22, wherein the minimum  
20 temperature is about 60°C, and the inclusion complex is disposed in at least one location in the electrically heated cigarette that reaches at least about 60°C during smoking of the cigarette.

27. The electrically heated cigarette of Claim 22, wherein the flavoring-  
25 release additive is disposed on an inner wrap surrounding a tobacco plug, on a tobacco-containing mat, and/or on an over wrap surrounding the mat.

-32-

28. The electrically heated cigarette of Claim 1, wherein the sorbent is fibers.

5 29. The electrically heated cigarette of Claim 28, wherein the fibers are continuous or non-continuous fibers.

30. The electrically heated cigarette of Claim 28, wherein the fibers are impregnated with at least one sorbent.

10 31. A method of making an electrically heated cigarette according to Claim 1, comprising incorporating into an electrically heated cigarette (a) the at least one sorbent, and (b) the flavoring-release additive including at least one flavoring releasable in the electrically heated cigarette upon the flavoring-release additive being heated to at least the minimum temperature.

15 32. A method of smoking the electrically heated cigarette of Claim 1, comprising heating a portion of the electrically heated cigarette to form smoke and drawing the smoke through the electrically heated cigarette, the sorbent removing at least one selected gas-phase constituent from mainstream smoke.

20 33. An electrical smoking system, comprising:  
a lighter; and  
at least one electrically heated cigarette including:  
at least one sorbent; and  
25 a flavoring-release additive including at least one flavoring which is releasable in the electrically heated cigarette upon the flavoring-release additive being heated to at least a minimum temperature.

-33-

34. An electrically heated cigarette, comprising:

at least one sorbent; and

at least one flavoring-release additive in a form selected from the group consisting of beads, film, and an inclusion complex, each flavoring-release additive including at least one flavoring releasable in the electrically heated cigarette upon the flavoring-release additive being heated to at least a minimum temperature.

35. The electrically heated cigarette of Claim 34, wherein the flavoring-release additive comprises at least two flavoring-release additives in the form of beads, film, and/or an inclusion complex, each flavoring-release additive having a different minimum temperature at which the flavoring is released during smoking of the electrically heated cigarette.

36. A method of making an electrically heated cigarette according to Claim 34, comprising incorporating into an electrically heated cigarette (a) the at least one sorbent, and (b) the at least one flavoring-release additive in the form of beads, film, and/or an inclusion complex, the flavoring-release additive including at least one flavoring releasable in the electrically heated cigarette upon the flavoring-release additive being heated to at least the minimum temperature.

37. A method of smoking the electrically heated cigarette of Claim 34, comprising heating a portion of the electrically heated cigarette to form smoke and drawing the smoke through the electrically heated cigarette, the sorbent removing at least one selected gas-phase constituent from mainstream smoke.




Fig. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5






FIG. 6

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number  
**WO 2004/041007 A3**


- (51) International Patent Classification<sup>7</sup>: **A24B 15/00**
- (21) International Application Number:  
PCT/US2003/034290
- (22) International Filing Date: 30 October 2003 (30.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/422,497 31 October 2002 (31.10.2002) US
- (71) Applicant (for all designated States except US): **PHILIP MORRIS PRODUCTS S.A.** [CH/CH]; Quai Jeanrenaud 3, CH-2000 Neuchatel (CH).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **WOODSON**, Beverley, C. [US/US]; 656 Lake Caroline Drive, Ruther Glen, VA 22546 (US). **NEWMAN**, Deborah, J. [US/US]; 11866 Centennial Road, Prince George, VA 23875 (US).
- (74) Agents: **SKIFF**, Peter, K. et al.; Burns, Doane, Swecker & Mathis, L.L.P., P.O. Box 1404, Alexandria, VA 22314-1404 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,

[Continued on next page]

(54) Title: **ELECTRICALLY HEATED CIGARETTE INCLUDING CONTROLLED-RELEASE FLAVORING**



(57) Abstract: Electrically heated cigarettes used in an electrical smoking system include a flavoring-release additive and sorbent effective to remove one or more gas-phase constituents of mainstream tobacco smoke. The flavoring-release additive includes at least one flavoring. The flavoring is released in the cigarette upon the flavoring-release additive reaching at least a minimum temperature during smoking. The flavoring-release additive can have various forms including, for example, beads, films and inclusion complexes. Electrical smoking systems including the electrically heated cigarettes, methods of making the cigarettes, and methods of smoking the cigarettes are also provided.



RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG,

KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the International search report:  
8 July 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US03/34290

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : A24B 15/00

US CL : 131/274, 275, 276, 200, 202, 203, 194

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 131/274, 275, 276, 200, 202, 203, 194

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
NONE

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 3,623,489 A (QUINN) 30 November 1971 (30.11.1971), see entire document.	1-32, 34-37
A		33

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

17 April 2004 (17.04.2004)

Date of mailing of the international search report

24 MAY 2004

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US

Commissioner for Patents

P.O. Box 1450

Alexandria, Virginia 22313-1450

Facsimile No. (703) 305-3230

Authorized officer

Dionne A. Walls

Telephone No. (571) 272-1700